



Female threaded and socket welded check valves



CL800 Bolted bonnet, full port and reducing port
Threaded, butt-welded or socket welded ends; design to BS5352


Specification (NPS)	R.P	1/2		3/4		1		1 1/4		2	
	F.P	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2		
Face to face	L	Lift	79	79	92	111	120	152	172	200	
		Swing	79	79	92	111	120	120	140	178	
Height	H	Lift	61	61	61	78	84	84	118	132	
		Swing	61	61	61	78	84	84	120	133	
Height (angle dimension)	d	Lift	7	9	13	17.5	23	30	35	46	
		Swing	8	10.5	13.5	18	24	29	36.5	45	
Weight(Kg)		Lift	1.2	1.5	1.7	3.3	4.2	4.2	10.5	12.5	
		Swing	1.4	1.5	1.7	3.3	4.2	4.2	8.5	10.9	

CL800 Welded bonnet, full port and reducing port
Threaded, butt-welded or socket welded ends; design to BS5352




Specification (NPS)	R.P	1/2		3/4		1		1 1/4		2		2 1/2	
	F.P	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2			
Face to face	L	79	79	92	111	120	152	172	200				
Height	H	61	61	61	78	84	103	118	132				
Height (angle dimension)	d	7	9	13	17.5	23	30	35	46				
Weight(Kg)		1.2	1.3	1.5	3.0	3.9	6.0	10	12				

CL900-CL1500 Bolted bonnet, full port and reducing port
Threaded, butt-welded or socket welded ends; design to BS5352



Specification (NPS)	R.P	1/2		3/4		1		1 1/4		2	
	F.P	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2		
Face to face	L	Lift	92	111	111	120	152	172	200		
		Swing	92	111	111	120	120	140	178		
Height	H	Lift	61	78	78	84	103	118	132		
		Swing	61	78	78	84	101	120	133		
Height (angle dimension)	d	Lift	7	12	15	20	28	32	40		
		Swing	8	10.5	13.5	18	24	29	45		
Weight(Kg)		Lift	1.5	3.4	3.3	4.2	6.3	10.5	12.5		
		Swing	1.5	3.4	3.3	4.2	5.0	8.5	10.9		

CL900-CL1500 Welded bonnet, full port and reducing port
Threaded, butt-welded or socket welded ends; design to BS5352



Specification (NPS)	R.P	1/2		3/4		1		1 1/4		2	
	F.P	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2		
Face to face	L	92	111	111	120	152	172	200			
Height	H	61	78	78	84	103	118	132			
Height (angle dimension)	d	7	12	15	20	28	32	40			
Weight(Kg)		1.3	3.1	3.1	3.9	5.8	10.0	11.5			